



## Вставка для ограничителя перенапряжения, класс D

Тип **SPDT3-335**  
Каталог № **170486**  
Eaton Каталог № **SPDT3-335**

### Программа поставок

Продукты		Устройство защиты от скачков напряжения (сетевой фильтр)
Область применения		Жилые здания Коммерческие здания Открытое пространство

### Технические характеристики согласно ETIM 6.0

Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems (EC000941)			
Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Surge protection device for power supply systems (ec1@ss8.1-27-13-08-05 [ACN278008])			
System configuration			-
Type of poles			1
Nominal discharge surge current (8/20)		kA	2.5
Nominal voltage AC		V	335
Nominal voltage DC		V	0
Max. continuous voltage AC		V	335
Max. continuous voltage DC		V	0
Max. PV-voltage		V	0
Voltage protection level		kV	1.6
Voltage protection level L-N		kV	0
Voltage protection level N-PE		kV	0
Short-circuit-proof			No
Mounting method			On basic element
Construction size			1 modular spacing
Max. conductor cross section solid (solid, stranded)		mm <sup>2</sup>	25
Max. conductor cross section flexible (fine-strand)		mm <sup>2</sup>	0
With remote signalling contact			No
Integrated backup fuse			No
Signalling at the device			Optic
Category type 2			No
Degree of protection (IP)			IP20