



Комплект ограничителей для сетей TN-S, класс B+C

Тип
Каталог №

SP-B+C/3+1
267510



Powering Business Worldwide™

Bauartnachweis nach IEC/EN 61439

Технические характеристики для подтверждения типа конструкции		
Номинальный ток для указания потери мощности	I _n	A 0
Потеря мощности на полюс, в зависимости от тока	P _{vid}	W 0
Потеря мощности оборудования, в зависимости от тока	P _{vid}	W 0
Статическая потеря мощности, не зависит от тока	P _{vs}	W 3
Способность отдавать потери мощности	P _{ve}	W 0
Мин. рабочая температура		°C -40
Макс. рабочая температура		°C 70

Технические характеристики согласно ETIM 6.0

Earthing, lightning and surge protection (EG000021) / Combined arrester for power supply systems (EC001457)		
Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Combined lightning current/surge arrester f. power supply s. (ecl@ss8.1-27-13-08-08 [ACN284008])		
System configuration DC		No
System configuration IT		Yes
System configuration TN		Yes
System configuration TN-C		No
System configuration TN-C-S		Yes
System configuration TN-S		Yes
System configuration TT		Yes
System configuration other		No
Number of poles		4
Lightning impulse current (10/350)	kA	35
Max. continuous voltage AC	V	0
Max. continuous voltage DC	V	0
Nominal voltage AC	V	0
Nominal voltage DC	V	0
Max. PV-voltage	V	0
Voltage protection level	kV	1.5
Voltage protection level L-N	kV	0
Voltage protection level N-PE	kV	0
Voltage protection level (DC+ - DC-)	kV	0
Voltage protection level (DC+/DC- - PE)	kV	0
Follow current extinguishing capability	kA	1
Specific energy (W/R)	kJ/Ohm	0
Max. conductor cross section solid (solid, stranded)	mm ²	35
Max. conductor cross section flexible (fine-strand)	mm ²	25
Mounting method	DIN rail (top hat rail) 35 mm	
Construction size	8 modular spacing	
Remote signalling	No	
Signalling at the device	Optic	
Test class	Type 1 + 2	
Exhausting	No	
Integrated backup fuse	No	
Energy-coordinated protection effect with regard to the terminal equipment	Yes	