



Модульный контактор 230В, 40А, 3НО+1НЗ

Тип **Z-SCH230/40-31**
Каталог № **248854**

Abbildung ähnlich

Bauartnachweis nach IEC/EN 61439

Технические характеристики для подтверждения типа конструкции			
Номинальный ток для указания потери мощности	I_n	A	40
Потеря мощности на полюс, в зависимости от тока	P_{vid}	W	0
Потеря мощности оборудования, в зависимости от тока	P_{vid}	W	11.6
Статическая потеря мощности, не зависит от тока	P_{vs}	W	0
Способность отдавать потери мощности	P_{ve}	W	0
Мин. рабочая температура		°C	-40
Макс. рабочая температура		°C	60
			0

Технические характеристики согласно ETIM 6.0

Devices for distribution board-/surface mounting (EG000062) / Installation contactor for distribution board (EC001653)			
Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Installation contactor for distribution board (ecl@ss8.1-27-14-23-08 [AFZ820012])			
Rated operating voltage	V		440 - 440
Rated operation current	A		40
Utility category			1
Rated excitation voltage	V		230 - 230
Voltage type (operating voltage)			AC
Voltage type (excitation voltage)			AC
Number of normally open contacts			3
Number of normally closed contacts			1
Max. incandescent lamp load	W		5520
Max. load fluorescent lamp	VA		2610
Max. load fluorescent lamp (Duo circuit)	VA		5336
Max. load fluorescent lamp (parallel compensated)	VA		2088
Slider for hand switch			No
Number of modular spacings			3
Built-in depth	mm		60
Additional equipment possible			Yes
Degree of protection (IP)			IP40