



Выключатель нагрузки, 2П, 40А

Тип **ZP-A40/2**
Каталог № **248264**

Технические характеристики согласно ETIM 6.0

| Devices for distribution board-/surface mounting (EG000062) / Main switch for distribution board (EC001545) | | | |
|---|--|----|----------------|
| Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Main switch for distribution board (ecI@ss8.1-27-14-23-01 [AFZ813011]) | | | |
| Switching function | | | Off switch |
| Number of normally open contacts | | | 0 |
| Number of normally closed contacts | | | 0 |
| Number of change-over contacts | | | 0 |
| Number of poles | | | 2 |
| Nominal rated current | | A | 40 |
| Nominal rated voltage | | V | 400 |
| Min. rated voltage | | V | 230 |
| Rated switching capacity | | kA | 0 |
| Short-circuit breaking capacity (Icw) | | kA | 3 |
| Voltage type | | | AC |
| Forced segregation (according to DIN VDE 0113) | | | No |
| With signal lamp | | | No |
| Colour calotte | | | Not applicable |
| Lamp type | | | Not applicable |
| Lamp socket | | | Not applicable |
| Max. lamp power | | W | 0 |
| Width in number of modular spacings | | | 2 |
| Built-in depth | | mm | 60 |
| Degree of protection (IP) | | | IP40 |