



Импульсное реле 48 В, 2НО

Тип **Z-S48/SS**
Каталог № **265536**

Abbildung ähnlich

Технические характеристики согласно ETIM 6.0

Devices for distribution board-/surface mounting (EG000062) / Latching relay (EC000188)			
Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Latching relay for distribution board (ec1@ss8.1-27-14-23-06 [AFZ818012])			
Function			-
Mounting method			DIN rail
Width in number of modular spacings			1
Built-in depth		mm	60
Number of normally open contacts			2
Number of normally closed contacts			0
Number of change-over contacts			0
Control voltage 1		V	48 - 48
Type of control voltage 1			AC
Frequency control voltage 1		Hz	50 - 50
Control voltage 2		V	24 - 24
Type of control voltage 2			DC
Frequency control voltage 2		Hz	50 - 50
Rated switch current		A	32
Supply voltage		V	250 - 250
Voltage type of supply voltage			AC
Max. incandescent lamp load		W	0
Max. load fluorescent lamp		VA	0
Max. load fluorescent lamp (Duo circuit)		VA	0
Max. load fluorescent lamp (parallel compensated)		VA	0
Max. switching current (cos phi = 0.6)		A	0
Manual operation possible			Yes