


Импульсное реле 230 В, перекидной контакт
Тип
Каталог №
Z-S230/W
265290
Bauartnachweis nach IEC/EN 61439

Технические характеристики для подтверждения типа конструкции

Мин. рабочая температура	°C	-20
Макс. рабочая температура	°C	45

Технические характеристики согласно ETIM 6.0

Devices for distribution board-/surface mounting (EG000062) / Latching relay (EC000188)

Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Latching relay for distribution board (ecl@ss8.1-27-14-23-06 [AFZ818012])

Function	Mechanical switch	
Mounting method	DIN rail	
Width in number of modular spacings	1	
Built-in depth	mm	60
Number of normally open contacts	0	
Number of normally closed contacts	0	
Number of change-over contacts	1	
Control voltage 1	V	230 - 230
Type of control voltage 1		AC
Frequency control voltage 1	Hz	50 - 50
Control voltage 2	V	0 - 0
Type of control voltage 2		AC
Frequency control voltage 2	Hz	0 - 0
Rated switch current	A	32
Supply voltage	V	250 - 250
Voltage type of supply voltage		AC
Max. incandescent lamp load	W	0
Max. load fluorescent lamp	VA	0
Max. load fluorescent lamp (Duo circuit)	VA	0
Max. load fluorescent lamp (parallel compensated)	VA	0
Max. switching current ($\cos \phi = 0.6$)	A	0
Manual operation possible		Yes

Размеры

