



## Держатель предохранителя 10x38, 3+N полюса

Тип  
Каталог №

C10-SLS/32/3N  
112224

### Технические характеристики согласно ETIM 6.0

Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnecter (ecI@ss8.1-27-37-14-01 [AKF058010])

|                                               |    |                  |
|-----------------------------------------------|----|------------------|
| Version as main switch                        |    | No               |
| Version as safety switch                      |    | No               |
| Max. rated operation voltage Ue AC            | V  | 690              |
| Rated permanent current Iu                    | A  | 32               |
| Rated operation power at AC-23, 400 V         | kW | 0                |
| Conditioned rated short-circuit current Iq    | kA | 100              |
| Rated short-time withstand current Icw        | kA | 0.3              |
| Suitable for fuses                            |    | Shape C1-C3      |
| Number of poles                               |    | 4                |
| With error protection                         |    | No               |
| Type of electrical connection of main circuit |    | Screw connection |
| Suitable for ground mounting                  |    | Yes              |
| Suitable for front mounting 4-hole            |    | No               |
| Suitable for busbar mounting                  |    | No               |
| Type of control element                       |    | -                |
| Position control element                      |    | Front side       |
| Motor drive optional                          |    | No               |
| Motor drive integrated                        |    | No               |
| Version as emergency stop installation        |    | No               |
| Degree of protection (IP), front side         |    | IP20             |