

Spring-cage connection terminal block- UJ1-2.5/3L - 021002



Spring-cage connection terminal block, rated voltage:660V , Max. operating current:24A, connection method : Spring-cage connection, number of connections : 3, crimping range : 0.2mm² -2.5mm² , thickness : 5mm, height:41mm, color : grey, mounting type : TH35-7.5、TH35-15

Product parameter

Parameter	Data
Packing unit (PCS)	/
NW per piece(g)	/
Layers	1
Number of connections	3
Rated cross section(mm ²)	2.5
Color	grey
Insulation material	PA
Flame retardant grade (UL94)	V0
Rated voltage(V)	660
Rated current(A)	24
Temperature of insulation material	-40°C~+125°C
Wire feed	Above the terminal

Product certification

Parameter	Data
Certification logo	CE
Certification logo	cUL [®] US

Parameter	Data
Certification logo	RoHS

Technical data

Parameter	Data
Connection Method	Spring-cage connection
Stripping length(mm)	7
Solid conductors(mm ²)	0.2-2.5
Solid conductors AWG	/
Stranded conductors(mm ²)	0.2-2.5
Stranded conductors AWG	/
Operating temperature (°C)	-40°C~+105°C
Ambient temperature (storage/transportation) (°C)	-25°C~+60°C
Relative humidity	30%~90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	50.2
Thickness(mm)	5
Height(mm)	41