

Screw clamping terminal block- UKJ-150-011015




Screw clamping terminal block, rated voltage:1000V , Max. operating current:309A, connection method : screw connection, number of connections : 2, crimping range : 35mm² -150mm² , thickness:32mm, height:111mm, color : grey, mounting type : TH35-7.5、TH35-15、G32-15、G32-18

Product parameter

Parameter	Data
Packing unit (PCS)	10
NW per piece(g)	3.79
Layers	1
Number of connections	2
Rated cross section(mm ²)	150
Color	grey
Insulation material	PA
Flame retardant grade (UL94)	V0
Rated voltage(V)	1000
Rated current(A)	309
Temperature of insulation material	-40°C~+125°C
Wire feed	Left and right side of the terminal

Product certification

Parameter	Data
Certification logo	
Certification logo	

Parameter	Data
	
Certification logo	
Certification logo	CCS
Certification logo	IECE_x
Certification logo	cUL[®] US
Certification logo	
Certification logo	RoHS

Technical data

Parameter	Data
Connection Method	Screw connection
Screw thread	M10
Stripping length(mm)	40
Tightening torque	25-30
Solid conductors(mm ²)	35-150
Stranded conductors(mm ²)	50-150

Parameter	Data
Operating temperature (°C)	-40°C～+105°C
Ambient temperature (storage/transportation) (°C)	-25°C～+60°C
Relative humidity	30%～90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	101.4
Thickness(mm)	32
Height(mm)	111