



Ограничитель перенапряжения, класс C, 1+N полюс

Тип **SPCT2-335-3+NPE**
Каталог № **167622**
Eaton Каталог № **SPCT2-335-3NPE**

Программа поставок

Продукты		Устройство защиты от скачков напряжения (сетевой фильтр)
Область применения		Жилые здания Коммерческие здания Открытое пространство

Технические характеристики согласно ETIM 6.0

Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems (EC000941)		
Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Surge protection device for power supply systems (ecl@ss8.1-27-13-08-05 [ACN278008])		
System configuration		-
Type of poles		3+N/PE
Nominal discharge surge current (8/20)	kA	20
Nominal voltage AC	V	335
Nominal voltage DC	V	0
Max. continuous voltage AC	V	335
Max. continuous voltage DC	V	0
Max. PV-voltage	V	0
Voltage protection level	kV	1.6
Voltage protection level L-N	kV	0
Voltage protection level N-PE	kV	0
Short-circuit-proof		No
Mounting method		DIN rail (top hat rail) 35 mm
Construction size		4 modular spacing
Max. conductor cross section solid (solid, stranded)	mm ²	25
Max. conductor cross section flexible (fine-strand)	mm ²	0
With remote signalling contact		No
Integrated backup fuse		No
Signalling at the device		Optic
Category type 2		Yes
Degree of protection (IP)		IP20