



## Ограничитель перенапряжения, класс С, 4 полюса

Тип **SPCT2-075/4**  
 Каталог № **167581**  
 Eaton Каталог № **SPCT2-075/4**

Abbildung ähnlich

### Программа поставок

Продукты		Устройство защиты от скачков напряжения (сетевой фильтр)
Область применения		Жилые здания Коммерческие здания Открытое пространство

### Технические характеристики согласно ETIM 6.0

Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems (EC000941)		
Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Surge protection device for power supply systems (ec1@ss8.1-27-13-08-05 [ACN278008])		
System configuration		-
Type of poles		4
Nominal discharge surge current (8/20)	kA	15
Nominal voltage AC	V	75
Nominal voltage DC	V	0
Max. continuous voltage AC	V	75
Max. continuous voltage DC	V	0
Max. PV-voltage	V	0
Voltage protection level	kV	0.55
Voltage protection level L-N	kV	0
Voltage protection level N-PE	kV	0
Short-circuit-proof		No
Mounting method		DIN rail (top hat rail) 35 mm
Construction size		4 modular spacing
Max. conductor cross section solid (solid, stranded)	mm <sup>2</sup>	25
Max. conductor cross section flexible (fine-strand)	mm <sup>2</sup>	0
With remote signalling contact		No
Integrated backup fuse		No
Signalling at the device		Optic
Category type 2		Yes
Degree of protection (IP)		IP20