



## Выключатель нагрузки, 3P+N, 40A

Тип **ZP-A40/3N**  
Каталог № **248266**

### Технические характеристики согласно ETIM 6.0

Devices for distribution board-/surface mounting (EG000062) / Main switch for distribution board (EC001545)

Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Main switch for distribution board (ecI@ss8.1-27-14-23-01 [AFZ813011])

|                                                |  |    |                |
|------------------------------------------------|--|----|----------------|
| Switching function                             |  |    | Off switch     |
| Number of normally open contacts               |  |    | 0              |
| Number of normally closed contacts             |  |    | 0              |
| Number of change-over contacts                 |  |    | 0              |
| Number of poles                                |  |    | 4              |
| Nominal rated current                          |  | A  | 40             |
| Nominal rated voltage                          |  | V  | 400            |
| Min. rated voltage                             |  | V  | 230            |
| Rated switching capacity                       |  | kA | 0              |
| Short-circuit breaking capacity (Icw)          |  | kA | 3              |
| Voltage type                                   |  |    | AC             |
| Forced segregation (according to DIN VDE 0113) |  |    | No             |
| With signal lamp                               |  |    | No             |
| Colour calotte                                 |  |    | Not applicable |
| Lamp type                                      |  |    | Not applicable |
| Lamp socket                                    |  |    | Not applicable |
| Max. lamp power                                |  | W  | 0              |
| Width in number of modular spacings            |  |    | 4              |
| Built-in depth                                 |  | mm | 60             |
| Degree of protection (IP)                      |  |    | IP40           |