



Соединительная шина, 2П, 63А, 2 модуля

Тип
Каталог №

EVG-2PHAS/4MODUL
268220

Abbildung ähnlich

Программа поставок

Основная функция			Сборная шина
Основная функция дополнительного оснащения			Сборная шина для линейного защитного автомата Сборная шина для дифференциальной защиты Сборная шина для переключателя комбинированной защиты FI/LS
Тип сборной шины			двухфазный
Ассортимент			EVG

Технические характеристики согласно ETIM 6.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss8.1-27-37-13-06 [ACN992008])			
Number of phases			2
Number of poles			2
Suitable for number of devices			2
Pitch dimensions		mm	0
Cross section		mm ²	10
Length		mm	65
Number of modular spacings			4
Rated permanent current I _u		A	63
Type of electric connection			Fork
Insulated			Yes
Rated surge voltage		kV	4
Conditioned rated short-circuit current I _q		kA	25
Max. rated operation voltage U _e		V	500
Rated short-time withstand current I _{cw}		kA	0
Suitable for devices with N-busbar			No
Suitable for devices with auxiliary switch			No