


Screw clamping terminal block-UKJ-4SK-TG- 011347



Screw clamping terminal block , rated voltage:500V , Max. operating current:16A, connection method : screw connection , number of connections : 2 , crimping range : 0.2mm<sup>2</sup> -6mm<sup>2</sup> , thickness:6.2mm , height:45.6mm , color : grey , mounting type : TH35-7.5、 TH35-15、 G32-15、 G32-18

### Product parameter

Parameter	Data
Packing unit (PCS)	/
NW per piece(g)	/
Layers	1
Number of connections	2
Rated cross section(mm <sup>2</sup> )	4
Color	grey
Insulation material	PA
Flame retardant grade ( UL94 )	V0
Rated voltage(V)	500
Rated current(A)	16
Temperature of insulation material	-40 ~ +125
Wire feed	Both sides of the terminal

### Product certification

Parameter	Data
Certification logo	<b>CE</b>
Certification logo	<b>RoHS</b>

### Technical data

Parameter	Data
Connection Method	Screw connection
Screw thread	M3
Stripping length(mm)	8mm
Tightening torque	0.6-0.8Nm
Solid conductors(mm <sup>2</sup> )	0.2-6
Stranded conductors(mm <sup>2</sup> )	0.2-4
Operating temperature ( )	-40 ~ +105
Ambient temperature (storage/transportation) ( )	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

## Dimension

Parameter	Data
Width(mm)	82
Thickness(mm)	6.2
Height(mm)	45.6