

Barrier screw terminal block- UBJ2-6-271005



Barrier screw terminal block , rated voltage:660V ,
Max. operating current:41A, connection
method : screw connection , number of
connections : 2 , crimping
range : 2.5mm² -6mm² , AWG : 14-10 , thick
ness : 13.5mm , height:45mm , color : Beige ,
mounting
type : TH35-7.5、 TH35-15、 G32-15、 G32-18

Product parameter

Parameter	Data
Packing unit (PCS)	/
NW per piece(g)	/
Layers	1
Number of connections	2
Rated cross section(mm ²)	6
Color	Beige
Insulation material	PA
Flame retardant grade (UL94)	V0
Rated voltage(V)	660
Rated current(A)	41
Temperature of insulation material	-40 ~ +125
Wire feed	Terminal side

Product certification

Parameter	Data
Certification logo	CE
Certification logo	cUL [®] US

Technical data

Parameter	Data
Connection Method	Screw connection
Screw thread	M5
Stripping length(mm)	12
Tightening torque	2.0-2.5
Solid conductors(mm ²)	2.5-6
Solid conductors AWG	14-10
Stranded conductors(mm ²)	2.5-6
Stranded conductors AWG	14-10
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	48.5
Thickness(mm)	13.5
Height(mm)	45