



## Вставка для ограничителя перенапряжения, класс С

Тип **SPCT2-075**  
 Каталог № **167577**  
 Eaton Каталог № **SPCT2-075**

Abbildung ähnlich

### Программа поставок

|                    |  |  |
|--------------------|--|--|
| Продукты           |  | Устройство защиты от скачков напряжения (сетевой фильтр)     |
| Область применения |  | Жилые здания<br>Коммерческие здания<br>Открытое пространство |

### Технические характеристики согласно ETIM 6.0

|  |                 |                   |
|--|-----------------|-------------------|
| Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems (EC000941)  |                 |                   |
| Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Surge protection device for power supply systems (ecl@ss8.1-27-13-08-05 [ACN278008]) |                 |                   |
| System configuration   |                 | -                 |
| Type of poles  |                 | 1                 |
| Nominal discharge surge current (8/20)   | kA              | 20                |
| Nominal voltage AC   | V               | 75                |
| Nominal voltage DC   | V               | 0                 |
| Max. continuous voltage AC   | V               | 75                |
| Max. continuous voltage DC   | V               | 0                 |
| Max. PV-voltage  | V               | 0                 |
| Voltage protection level   | kV              | 0.55              |
| Voltage protection level L-N   | kV              | 0                 |
| Voltage protection level N-PE  | kV              | 0                 |
| Short-circuit-proof  |                 | No                |
| Mounting method  |                 | On basic element  |
| Construction size  |                 | 1 modular spacing |
| Max. conductor cross section solid (solid, stranded)   | mm <sup>2</sup> | 25                |
| Max. conductor cross section flexible (fine-strand)  | mm <sup>2</sup> | 0                 |
| With remote signalling contact   |                 | No                |
| Integrated backup fuse   |                 | No                |
| Signalling at the device   |                 | Optic             |
| Category type 2  |                 | Yes               |
| Degree of protection (IP)  |                 | IP20              |