



Выключатель-разъединитель, низкое напряжение, 630 A, AC 690 V, NH3, AC22B, 3P, IEC

Каталог № **EBH303TM2**

Программа поставок

Программа поставок			Принадлежности к предохранителю
Основная функция			Выключатель-разъединитель
Область применения			низкое напряжение
Номинальный ток	I	A	630
Номинальное напряжение			AC 690 V
Типоразмер			NH3
Категория применения			AC22B
Описание			тип монтажной панели Винты M12
Защита			IP20
Количество полюсов			3P
возможно использование для типоразмеров/оборудования			Предохранители NH3
Стандарт/сертификат			IEC
Форма			горизонтально
Стандарты/предписания			IEC 60947-1 IEC 60947-3

Технические характеристики согласно ETIM 6.0

Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnecter (ecI@ss8.1-27-37-14-01 [AKF058010])			
Version as main switch			No
Version as safety switch			No
Max. rated operation voltage Ue AC		V	690
Rated permanent current Iu		A	630
Rated operation power at AC-23, 400 V		kW	252
Conditioned rated short-circuit current Iq		kA	25
Rated short-time withstand current Icw		kA	25
Suitable for fuses			NH3
Number of poles			3
With error protection			No
Type of electrical connection of main circuit			Screw connection
Suitable for ground mounting			No
Suitable for front mounting 4-hole			Yes
Suitable for busbar mounting			No
Type of control element			Cover grip
Position control element			Front side
Motor drive optional			No
Motor drive integrated			No
Version as emergency stop installation			No
Degree of protection (IP), front side			IP30