

Spring-cage connection terminal block- UJ4-2.5/3 - 040010



Spring-cage connection terminal block , rated voltage:660V , Max. operating current:24A, connection method : / , number of connections : / , crimping range : 0.2mm² -2.5mm² , thickness : 205mm , height:125mm , color : grey , mounting type : the screw fixed

Product parameter

Parameter	Data
Packing unit (PCS)	/
NW per piece(g)	/
Rated cross section(mm ²)	2.5
Color	grey
Insulation material	PA
Flame retardant grade (UL94)	V0
Rated voltage(V)	660
Rated current(A)	24
Temperature of insulation material	-40 ~ +125
Wire feed	Above the terminal

Product certification

Parameter	Data
Certification logo	CE
Certification logo	

Parameter	Data
	RoHS

Technical data

Parameter	Data
Stripping length(mm)	8
Solid conductors(mm ²)	0.2-2.5
Solid conductors AWG	/
Stranded conductors(mm ²)	0.2-2.5
Stranded conductors AWG	/
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	103
Thickness(mm)	205
Height(mm)	125