



Комплект разрядников 460В, 4 полюса, класс В+С

Тип **SPCT2-460/4**
 Каталог № **167611**
 Eaton Каталог № **SPCT2-460/4**

Abbildung ähnlich

Программа поставок

Продукты		Устройство защиты от скачков напряжения (сетевой фильтр)
Область применения		Жилые здания Коммерческие здания Открытое пространство

Технические характеристики согласно ETIM 6.0

Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems (EC000941)			
Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Surge protection device for power supply systems (ec1@ss8.1-27-13-08-05 [ACN278008])			
System configuration			-
Type of poles			4
Nominal discharge surge current (8/20)		kA	20
Nominal voltage AC		V	460
Nominal voltage DC		V	0
Max. continuous voltage AC		V	460
Max. continuous voltage DC		V	0
Max. PV-voltage		V	0
Voltage protection level		kV	2.2
Voltage protection level L-N		kV	0
Voltage protection level N-PE		kV	0
Short-circuit-proof			No
Mounting method			DIN rail (top hat rail) 35 mm
Construction size			4 modular spacing
Max. conductor cross section solid (solid, stranded)		mm ²	25
Max. conductor cross section flexible (fine-strand)		mm ²	0
With remote signalling contact			No
Integrated backup fuse			No
Signalling at the device			Optic
Category type 2			Yes
Degree of protection (IP)			IP20