


Barrier screw terminal block-
UBJ2-2.5S3-271021




Barrier screw terminal block , rated voltage:660V ,
Max. operating current:24A, connection
method : screw connection , number of
connections : 6 , crimping
range : 1mm² -2.5mm² , AWG : 16-14 , thick
kness : 9.6mm , height:529mm , color : Beige ,
mounting
type : TH35-7.5、 TH35-15、 G32-15、 G32-18

Product parameter

Parameter	Data
Packing unit (PCS)	/
NW per piece(g)	/
Layers	1
Number of connections	6
Rated cross section(mm ²)	2.5
Color	Beige
Insulation material	PA
Flame retardant grade (UL94)	V0
Rated voltage(V)	660
Rated current(A)	24
Temperature of insulation material	-40 ~ +125
Wire feed	Terminal side

Product certification

Parameter	Data
Certification logo	

Technical data

Parameter	Data

Parameter	Data
c	Screw connection
Screw thread	M4
Stripping length(mm)	10
Tightening torque	1.5-1.8
Solid conductors(mm ²)	1-2.5
Solid conductors AWG	16-14
Stranded conductors(mm ²)	1-2.5
Stranded conductors AWG	16-14
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	62.2
Thickness(mm)	9.6
Height(mm)	59