

Push-in terminal blocks-UJ6-16-421514



Terminal block, Rated voltage(V): 1000V. Rated current: 76A, connection methods: circlip connection, number of connection: 2, 1.5mm² -25mm², AWG : 16-4, thickness 12.2mm, height 50.6mm, color: grey, mounting rail: TH35-7.5、TH35-15.

Product parameter

Parameter	Data
Packing unit(pcs)	30
NW per piece(g)	35.1
Layers	1
Number of connections	2
Rated cross section(mm ²)	16
Color	grey
Insulation material	PA
Flame retardant grade	V0
Rated voltage(V)	1000
Rated current(A)	76
Temperature of insulation material	-40 ~ +125
Wire feed	Above the terminal

Product certification

Parameter	Data
Certification logo	CE
Certification logo	cUL [®] US
Certification logo	

Parameter	Data
	RoHS

Technical data

Parameter	Data
Connection Method	Push in connection
Stripping length(mm)	22
Solid conductors(mm ²)	1.5-25
Solid conductors AWG	16-4
Stranded conductors(mm ²)	1.5-16
Stranded conductors AWG	16-6
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +55
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	74
Thickness(mm)	12.2
Height(mm)	50.6