



## Супрессор с RC цепью, 12-250В AC

Тип **Z-RC/230**  
Каталог № **101428**

### Bauartnachweis nach IEC/EN 61439

| Технические характеристики для подтверждения типа конструкции |           |    |     |
|---------------------------------------------------------------|-----------|----|-----|
| Номинальный ток для указания потери мощности                  | $I_n$     | A  | 0   |
| Потеря мощности на полюс, в зависимости от тока               | $P_{vid}$ | W  | 0   |
| Потеря мощности оборудования, в зависимости от тока           | $P_{vid}$ | W  | 0   |
| Статическая потеря мощности, не зависит от тока               | $P_{vs}$  | W  | 1.2 |
| Способность отдавать потери мощности                          | $P_{ve}$  | W  | 0   |
| Мин. рабочая температура                                      |           | °C | -40 |
| Макс. рабочая температура                                     |           | °C | 60  |
|                                                               |           |    | 0   |

### Технические характеристики согласно ETIM 6.0

| Devices for distribution board-/surface mounting (EG000062) / Auxiliary contact unit for distribution board (EC001286)                                                                                         |  |   |                          |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|---|--------------------------|
| Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss8.1-27-14-35-02 [AKE327010]) |  |   |                          |
| Device fitting                                                                                                                                                                                                 |  |   | Auxiliary switch / relay |
| Additional equipment                                                                                                                                                                                           |  |   | -                        |
| Attached at delivery                                                                                                                                                                                           |  |   | No                       |
| Assembly width (TE)                                                                                                                                                                                            |  |   | 2                        |
| Number of normally open contacts                                                                                                                                                                               |  |   | 0                        |
| Number of normally closed contacts                                                                                                                                                                             |  |   | 0                        |
| Number of change-over contacts                                                                                                                                                                                 |  |   | 0                        |
| Number of fault-signal switches                                                                                                                                                                                |  |   | 0                        |
| Rated switch current                                                                                                                                                                                           |  | A | 0                        |
| Nominal rated voltage                                                                                                                                                                                          |  | V | 250                      |
| Control voltage type                                                                                                                                                                                           |  |   | AC                       |
| With autotest for earth leakage function                                                                                                                                                                       |  |   | No                       |
| Suitable for max. number of poles main contact unit (total)                                                                                                                                                    |  |   | 0                        |
| Suitable for max. current main contact unit                                                                                                                                                                    |  | A | 0                        |