



Ограничитель перенапряжения, класс C, 2 полюса

Тип SPCT2-385/2
Каталог № 167604
Eaton Каталог № SPCT2-385/2

Abbildung ähnlich

Программа поставок

| | |
|--------------------|--|
| Продукты | Устройство защиты от скачков напряжения (сетевой фильтр) |
| Область применения | Жилые здания Коммерческие здания Открытое пространство |

Технические характеристики согласно ETIM 6.0

| | | |
|--|-----------------|-------------------------------|
| Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems (EC000941) | | |
| Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Surge protection device for power supply systems (ecl@ss8.1-27-13-08-05 [ACN278008]) | | |
| System configuration | | - |
| Type of poles | | 2 |
| Nominal discharge surge current (8/20) | kA | 20 |
| Nominal voltage AC | V | 385 |
| Nominal voltage DC | V | 0 |
| Max. continuous voltage AC | V | 385 |
| Max. continuous voltage DC | V | 0 |
| Max. PV-voltage | V | 0 |
| Voltage protection level | kV | 1.8 |
| Voltage protection level L-N | kV | 0 |
| Voltage protection level N-PE | kV | 0 |
| Short-circuit-proof | | No |
| Mounting method | | DIN rail (top hat rail) 35 mm |
| Construction size | | 2 modular spacing |
| Max. conductor cross section solid (solid, stranded) | mm ² | 25 |
| Max. conductor cross section flexible (fine-strand) | mm ² | 0 |
| With remote signalling contact | | No |
| Integrated backup fuse | | No |
| Signalling at the device | | Optic |
| Category type 2 | | Yes |
| Degree of protection (IP) | | IP20 |