



Карты памяти , SD, для XC100/200 и XV100

Тип **XT-МЕМ-ММ32М**
Каталог № **262731**

Программа поставок

Принадлежности			Карты памяти
			для сохранения программ, данных, рецептов
Описание			256 МБ
Применяемое для			MFD4 XC100 XC200 XC121
Information relevant for export to North America			
Product Standards IEC: see Technical Data; UL508; CSA-C22.2 No. 0-M; CSA-C22.2 No. 142-M; CE marking			
UL File No. E135462			
UL Category Control No. NRAQ			
CSA File No. 012528			
CSA Class No. 2252-01			
North America Certification UL listed, CSA certified			
Degree of Protection IEC: IP20, UL/CSA Type: -			

Bauartnachweis nach IEC/EN 61439

Технические характеристики для подтверждения типа конструкции			
Мин. рабочая температура		°C	0
Макс. рабочая температура		°C	55

Технические характеристики согласно ETIM 6.0

PLC's (EG000024) / PLC memory card (EC000192)			
Electric engineering, automation, process control engineering / Control / Programmable logic control (SPS) / SPS memory unit (ecl@ss8.1-27-24-22-12 [AKE535011])			
Type of memory			-
Memory size		kByte	32000

Апробации

Product Standards			IEC: see Technical Data; UL508; CSA-C22.2 No. 0-M; CSA-C22.2 No. 142-M; CE marking
UL File No.			E135462
UL Category Control No.			NRAQ
CSA File No.			012528
CSA Class No.			2252-01
North America Certification			UL listed, CSA certified
Specially designed for North America			No
Current Limiting Circuit-Breaker			No
Degree of Protection			IEC: IP20, UL/CSA Type: -