


Spring-cage connection terminal block- UJ2-1.5N - 441033



Spring-cage connection terminal block , rated voltage:400V , Max. operating current:17.5A, connection method : Spring-cage connection , number of connections : 2 , crimping range : 0.08mm² -1.5mm² , thickness : 5mm , height:17.2mm , color : grey , mounting type : /

Product parameter

Parameter	Data
Packing unit (PCS)	/
NW per piece(g)	/
Layers	1
Number of connections	2
Rated cross section(mm ²)	1.5
Color	grey
Insulation material	PA
Flame retardant grade (UL94)	V0
Rated voltage(V)	400
Rated current(A)	17.5
Temperature of insulation material	-40 ~ +125
Wire feed	Above the terminal

Product certification

Parameter	Data
Certification logo	RoHS

Technical data

Parameter	Data
Connection Method	Spring-cage connection
Stripping length(mm)	8-9
Solid conductors(mm ²)	0.08-1.5

Parameter	Data
Solid conductors AWG	/
Stranded conductors AWG	/
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	25
Thickness(mm)	5
Height(mm)	17.2