

Push-in terminal blocks-UJ6-4/2 2-PV-421542



Terminal block, Rated voltage: 800V, Rated current: 32A, connection methods: circlip connection, number of connection: 4, crimping range: 0.2mm² -6mm², AWG : 14-10, thickness 6.2mm, height 45.8mm, color: grey, mounting rail: TH35-7.5、TH35-15.

Product parameter

Parameter	Data
Packing unit(pcs)	40
NW per piece(g)	15.8
Layers	2
Number of connections	4
Rated cross section(mm ²)	4
Color	grey
Insulation material	PA
Flame retardant grade	V0
Rated voltage(V)	800
Rated current(A)	32
Temperature of insulation material	-40 ~ +125
Wire feed	Above the terminal

Product certification

Parameter	Data
Certification logo	CE
Certification logo	RoHS

Technical data

Parameter	Data
Connection Method	Push in connection
Stripping length(mm)	13
Solid conductors(mm ²)	0.2-6
Solid conductors AWG	14-10
Stranded conductors(mm ²)	0.2-4
Stranded conductors AWG	14-10
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +55
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	83.6
Thickness(mm)	6.2
Height(mm)	45.8