

Screw clamping terminal block-UKJ-240-011062



Screw clamping terminal block , rated voltage:1000V , Max. operating current:415A, connection method : screw connection , number of connections : 2 , crimping range : 70mm² -240mm² , thickness:37.6mm , height:126mm , color : grey , mounting type : TH35-7.5、 TH35-15、 G32-15、 G32-18

Product parameter

Parameter	Data
Packing unit (PCS)	4
NW per piece(g)	/
Layers	1
Number of connections	2
Rated cross section(mm ²)	240
Color	grey
Insulation material	PA
Flame retardant grade (UL94)	V0
Rated voltage(V)	1000
Rated current(A)	415
Temperature of insulation material	-40 ~ +125
Wire feed	Left and right side of the terminal

Product certification

Parameter	Data
Certification logo	CE
Certification logo	

Parameter	Data
	
Certification logo	
Certification logo	CCS
Certification logo	IECE_x
Certification logo	cUL[®] US
Certification logo	
Certification logo	RoHS

Technical data

Parameter	Data
Connection Method	Screw connection
Screw thread	M10
Stripping length(mm)	40
Tightening torque	25-30
Solid conductors(mm ²)	70-240
Stranded conductors(mm ²)	70-240

Parameter	Data
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	100
Thickness(mm)	100
Height(mm)	100