



Klemsan®

808452 TERMAL ROLL YAZICI

Thermo Roll ПРИНТЕР

Общая информация про продукт

	KL-Tx300 (No display)
	300
	Thermal Transfer & Thermal Direct
	152 mm/s (6")
	106 mm/s (4,17")
	11.430 mm/s (450")
	Double- walled folding design made of plastic
Размеры	226 mm (W) x 198 mm (H) x 332 mm (D) mm
Размеры	8,90" (W) x 7,80" (H) x 13,07" (D) Inch
вес	3,75 kg kg
Этикетка Rolls	127 mm (5") outer diameter
лента	300 m meters max. length; 67 mm outer diameter; 1" core diameter
Лента ширина	40 mm to 110 mm (1,6" to 4,3")
процессор	32-bit RISC CPU
объем памяти	128 MB Flash Memory, 128 MB SDRAM Memory, MicroSD Flash memory expansion up to 32 GB
Соединение	USB 2.0; RS-232; Ethernet 10/100 Mbps; USB Host; Centronics (optional); External Bluetooth (server option); •External 802.11 b/g/n wireless module (server option)
Кнопки управления LED/ LCD	Power switch; 1 Feed / Pause Button; LED panel with 8 large symbols / icons
Мощность	Input: AC 100-240V, 2.5A, 50-60Hz Output: DC 24V, 3.75A, 90W
датчиков	• Transmissive sensor for label gaps; Adjustable reflective marking sensor (Blackmark); Film rotation; Print head open
Часы реального времени	Optional
Интернет шрифты	• 8 alphanumeric bitmap fonts; Monotype Image® Truetype font set with a scalable CG Triumvirate bold condensed font
	1D Barcode: Code 39, Code 93, Code 128UCC, Code 128 Charset A, B, C, Codebar, Interleave 2/5, EAN-8, EAN-13, EAN-128, UPCA,UPC-E,

Штрих-код	EAN and UPC 2 (5) Extension, MSI, PLESSEY, POSTNET, ITF14, EAN 14, Code 11, TELEPEN, TELEPENN, PLANET, Code 49, Deutsche Post Identcode 2D Barcode: TLC39, CODABLOCK F, PDF-417, Maxicode, DataMatriz, QR Code, Aztec, Micro PDF 417, GS1 DataBar (RSS Barcode)
Шрифт / Штрих-код	Rotation 0°, 90°, 180°, 270°
Команда принтера	TSPL-EZTM (Compatible with EPL, ZPL, ZPL II)
Тип материала	Endless, pre-punched, black marking, leporello-folded, notch, bracelet (externally wound)
Ширина материала	19 to 112 mm (0,75" to 4,4")
Толщина материала	3 to 11.430 mm; (0,1" to 450")
Материал Диаметр сердцевины	25,4 to 38,1 mm (1" to 1.5")
Длина этикетки	3 to 11.430 mm; (0,1" to 450")
экологическая	Operation: 5 to 40°C, 25 to 85% humidity (non-condensing)
условия	Storage: -40 to 60°C, 10 to 90% humidity (non-condensing)
Инструкции по технике безопасности	FCC Klasse B, CE Klasse B, RCM, UL, cUL, TÜV/Safety, CCC https://cevirsozluk.com/
Защита окружающей среды	Corresponds to RoHS, WEEE
аксессуары	Windows Software CD, Quick Start Guide; USB Cable; Power Cord; External Universal Power Supply
Гарантия	Printer: 2 years
дополнительные аксессуары	Centronics Parallel-Creation; Real-time Clock; 3.5" Colour TFT display (with real time clock); Ribbon End Sensor; Centronics Parallel Interface; Guillotine Knife (full)
Операция Дополнительные аксессуары	Bluetooth module (serial interface); 802.11 b/g/n wireless module (serial port); External roller holder; KP-200 Plus keyboard with display; KU-007 Plus Programmable keyboard



Order Info

808452 Thermo Roll ПРИНТЕР