

Push-in terminal blocks-UJ6-6/2 × 2JD - 421508



Terminals block, connection methods: circlip connection, number of connection: 4, crimping range: 0.5mm² -10mm², thickness 8.2mm, height 42.2mm, color: yellow green, mounting rail: TH35-7.5、TH35-15.

Product parameter

Parameter	Data
Packing unit(pcs)	28
NW per piece(g)	25.7
Layers	1
Number of connections	4
Rated cross section(mm ²)	6
Color	yellow green
Insulation material	PA
Flame retardant grade	V0
Rated voltage(V)	/
Rated current(A)	/
Temperature of insulation material	-40 ~ +125
Wire feed	Above the terminal

Product certification

Parameter	Data
Certification logo	CE
Certification logo	cUL [®] US
Certification logo	

Parameter	Data
	RoHS

Technical data

Parameter	Data
Connection Method	Push in connection
Stripping length(mm)	16
Solid conductors(mm ²)	0.5-10
Solid conductors AWG	14-8
Stranded conductors(mm ²)	0.5-6
Stranded conductors AWG	14-10
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +55
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	94
Thickness(mm)	8.2
Height(mm)	42.2