



Опорная пластина, ХЕ, для ШхГ=1200х35мм, IP20

Тип
Каталог №

XSPBAC1201
107691

Программа поставок

Ассортимент		Распределитель системы управления XVTL
Основная функция		Дополнительное оснащение
Функция продукции		Дополнительное оснащение
Принадлежности		Нижние пластины
Отдельное устройство/законченное устройство		Дополнительное оснащение
Описание		Нижние пластины в виде глухих панелей регулировка в диапазоне 60 - 75 мм При использовании 2 XSPBA... возможна установка кабельных вводов < 50 мм При использовании XSPBA... в комбинации с XVTL-BP/JL возможна установка кабельных вводов 50 - 80 мм
Функция		для выгородки вниз и для ввода проводки
Материал		Листовая сталь 1,5 мм
Качество поверхности		RAL 7035, светло-серый
Информация о комплекте поставки		включая винты
подходит для глубины		35
подходит для ширины		1200
Cableway		< 50 мм

Технические характеристики согласно ETIM 6.0

Cabinet enclosures (EG000011) / Component for installation (switchgear cabinet) (EC002620)			
Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Switching cabinet, housing, rack (accessories) / Component for installation (electrical cabinet) (ecl@ss8.1-27-18-92-61 [ACN627008])			
Model			Floor plate
Suitable for enclosure building width		mm	1200
Suitable for enclosure building height		mm	0
Suitable for enclosure building depth		mm	35
Width		mm	1100
Height		mm	20
Depth		mm	35
Material			Metal
Colour			Grey
RAL-number			7035