



5	Pin header	Copper alloy	Sn plated
4	Cage	Copper alloy	M2.5/Ni Plated
3	Screw	Steel	M2.5/Zn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:		B	C
额定电压/电涌/Rated Voltage(V)/Current(A)	300/15	/	300/10
EC 标准/EC Standard:			
过压类别/Overvoltage Category/污秽等级/ Pollution Degree	III/3	III/2	II/2
额定电压/电涌/Rated Voltage(V)/Current(A)	/	250/24	/
工频耐压/Withstanding Voltage(V/Min)	/	AC2000	/
螺丝扭矩/Torque Tightening(N·m/Lb·in)	M2.5, 0.4/3.54		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.5~2.5/28~12		
间距/Pitch(mm)/线数范围/Poles	5.0/N=02~20P		
剥线长度/Stripping length(mm)	5-6		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

MATERIAL:	
MAT NO.:	
STATUS:	
APPD:	Li GL 2020.06.19
CHKD:	Mao J 2020.06.19
DRFT:	Lin 2007.03.22
NAME:	NINGBO DEGSON ELECTRICAL CO., LTD
DRAWING NO.:	DG632-5.0-C01
TYPE:	CUSTOMER DRAWING
SCALE:	3:1
REV	TO
1/1	

REV	ECN	DESCRIPTION	DRFT	DATE	SIZE:A4	TYPE	SCALE	SHEET
					1/1	CUSTOMER DRAWING	3:1	1/1

A B C D

1 2 3 4 5 6

A B C D