

Screw clamping terminal block-
USK-4 / 2 × 2- 281008





Screw clamping terminal block , rated voltage:500V , Max. operating current:32A, connection method : screw connection , number of connections : 4 , crimping range : 0.5mm² -4mm² ,AWG : 20-12 , thickness:6mm , height:56mm , color : Beige , mounting type : TH35-7.5、 TH35-15、 G32-15、 G32-18

Product parameter

Parameter	Data
Packing unit (PCS)	100
NW per piece(g)	13.85
Layers	2
Number of connections	4
Rated cross section(mm ²)	4
Color	Beige
Insulation material	PA
Flame retardant grade (UL94)	V0
Rated voltage(V)	500
Rated current(A)	32
Temperature of insulation material	-40 ~ +125
Wire feed	Terminal side

Product certification

Parameter	Data
Certification logo	
Certification logo	

Technical data

Parameter	Data
Connection Method	Screw connection
Screw thread	M3
Stripping length(mm)	10
Tightening torque	0.5-1.0
Solid conductors(mm ²)	0.5-4
Solid conductors AWG	20-12
Stranded conductors(mm ²)	1.5-4
Stranded conductors AWG	20-12
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	55.5
Thickness(mm)	6
Height(mm)	56