


Spring-cage connection terminal block- UJ2-1.5/2×2 - 441004



Spring-cage connection terminal block, rated voltage:400V , Max. operating current:17.5A, connection method : Spring-cage connection, number of connections : 2, crimping range : 0.08mm² -1.5mm² , thickness : 8mm , height:17.2mm, color : grey, mounting type : TH35-7.5

Product parameter

Parameter	Data
Packing unit (PCS)	/
NW per piece(g)	/
Layers	1
Number of connections	2
Rated cross section(mm ²)	1.5
Color	grey
Insulation material	PA
Flame retardant grade (UL94)	V0
Rated voltage(V)	400
Rated current(A)	17.5
Temperature of insulation material	-40°C~+125°C
Wire feed	Above the terminal

Product certification

Parameter	Data
Certification logo	CE
Certification logo	RoHS

Technical data

Parameter	Data
Connection Method	Spring-cage connection
Stripping length(mm)	8-9
Solid conductors(mm ²)	0.08-1.5
Solid conductors AWG	/
Stranded conductors(mm ²)	0.08-1.5
Stranded conductors AWG	/
Operating temperature (°C)	-40°C~+105°C
Ambient temperature (storage/transportation) (°C)	-25°C~+60°C
Relative humidity	30%~90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	25
Thickness(mm)	8
Height(mm)	17.2