



Выключатель нагрузки, 32A, 4 полюса

Тип **IS-32/4**
Каталог № **276269**
Eaton Каталог № **IS-32/4**

Abbildung ähnlich

Программа поставок

Основная функция			Главные переключатели для работы под нагрузкой
Полюсы			4-полюсн.
Применение			Коммутационные устройства для промышленного оборудования и специальных зданий
Расчетный рабочий ток	I_n	A	32
Ассортимент			IS
графические условные обозначения			

Bauartnachweis nach IEC/EN 61439

Технические характеристики для подтверждения типа конструкции			
Мин. рабочая температура		°C	-5
Макс. рабочая температура		°C	40

Технические характеристики согласно ETIM 6.0

Devices for distribution board-/surface mounting (EG000062) / Main switch for distribution board (EC001545)			
Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Main switch for distribution board (ec1@ss8.1-27-14-23-01 [AFZ813011])			
Switching function			-
Number of normally open contacts			0
Number of normally closed contacts			0
Number of change-over contacts			0
Number of poles			4
Nominal rated current		A	32
Nominal rated voltage		V	240
Min. rated voltage		V	240
Rated switching capacity		kA	0
Short-circuit breaking capacity (Icw)		kA	2
Voltage type			AC
Forced segregation (according to DIN VDE 0113)			No
With signal lamp			No
Colour calotte			Not applicable
Lamp type			Not applicable
Lamp socket			Not applicable
Max. lamp power		W	0
Width in number of modular spacings			4
Built-in depth		mm	69.5
Degree of protection (IP)			IP40

