



Модульная кнопка 4НО

Тип **Z-S/4S**
Каталог № **248335**

Abbildung ähnlich

Технические характеристики согласно ETIM 6.0

Devices for distribution board-/surface mounting (EG000062) / Main switch for distribution board (EC001545)

Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Main switch for distribution board (ec1@ss8.1-27-14-23-01 [AFZ813011])

| | | | |
|--|--|----|----------------|
| Switching function | | | Control switch |
| Number of normally open contacts | | | 4 |
| Number of normally closed contacts | | | 0 |
| Number of change-over contacts | | | 0 |
| Number of poles | | | 0 |
| Nominal rated current | | A | 16 |
| Nominal rated voltage | | V | 230 |
| Min. rated voltage | | V | 0 |
| Rated switching capacity | | kA | 20 |
| Short-circuit breaking capacity (Icw) | | kA | 10 |
| Voltage type | | | AC |
| Forced segregation (according to DIN VDE 0113) | | | No |
| With signal lamp | | | No |
| Colour calotte | | | Not applicable |
| Lamp type | | | Not applicable |
| Lamp socket | | | Not applicable |
| Max. lamp power | | W | 0 |
| Width in number of modular spacings | | | 1 |
| Built-in depth | | mm | 80 |
| Degree of protection (IP) | | | IP40 |