

Product Data Sheet

Specifications



Modular Switch Disconnectors (MSDs) VN-63N PROXIMA EKF

Standards: IEC 60947-3

Product Line	PROXIMA
Series Name	VN-63N
Device Application	Distribution
Input Voltage Type	AC
Rated Voltage, AC [Ue, V]	1P, 2P: 220 / 230 / 240 3P, 4P: 380 / 400 / 415
Frequency [Hz]	50 / 60
Poles	1P, 2P, 3P, 4P
Rated Current [In, A]	16, 20, 25, 32, 40, 63
Rated Short-Time Withstand Current, 1s [Icw, kA]	1
Rated Making Capacity [Icm, kA]	6
Rated Impulse Withstand Voltage [Uimp, kV]	6
Energy Limiting Class	3
Mechanical Endurance [O-C Cycles]	20 000
Electrical Endurance [O-C Cycles]	10 000
Tightening Torque, Max. [N·m]	3
Degree of Protection	IP20
Operation Ambient Temperatures [°C]	-25 to +55
Cross-Section of Connected Wires [mm²]	1 to 25
Contact Position Indicator	Yes
Auxiliaries	Yes
Mounting Support	DIN rail
Weight, Max. [1P, Kg]	0,0725
Color	Grey (RAL 7035/Pantone Cool Gray 2C)
Warranty Period	7 years



EKF

EKF ELECTRICAL SOLUTION – FZCO
Dubai Silicon Oasis, DDP, Building A2,
Dubai, United Arab Emirates
P.O. Box 342001

www.global.ekfgroup.com

**ENERGY
KNOWLEDGE
FUTURE**

Page 2 of 2

Overall Dimensions (mm)

