



Профильная клемма, 41x20 - 42 мм

Тип
Каталог №

AKP800
107198

Программа поставок

Ассортимент			Система 60 мм Система 185 мм
Подассортимент			Профильные зажимы
Описание			Соединение без отверстий на токовых шинах При параллельном соединении пластинчатых медных шин следует использовать распорки
ширина		мм	72
Расчетный рабочий ток	I_e	A	1600
электропроводник			800 мм ² , клеммный отсек 41 x 20 - 42 мм 
Cu factor		kg	0,20
Применяемое для			Двойной Т-образный профиль
указания	 Круглый провод одножильный  Круглый провод тонкожильный с правильно запрессованной оконечной муфтой  Круглый провод с несколькими жилами  Секторный провод одножильный  Секторный провод с несколькими жилами  Медная полоса  Медная шина		

Апробации

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E307559
UL Category Control No.			NMTR2, NMTR8
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL recognized, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC
Degree of Protection			Feeder circuits