

Дверь , IP55 , ДхШ = 1540x593mm

Тип **XVTL-D-6-16**
Каталог № **114637**



Программа поставок

Ассортимент		Распределитель системы управления XVTL
Основная функция		Платы расширения
Функция продукции		Дополнительное оснащение
Принадлежности		Двери
Отдельное устройство/законченное устройство		Модульная система
Описание		замкнут Одностворчатые двери 3-точечное запирание с поворотным рычажным запором
Материал		Листовая сталь 1,25 мм
Качество поверхности		Полиэфирное порошковое покрытие RAL 7035, светло-серый RAL 9016, дорожный белый
Информация о комплекте поставки		включая винты
Класс защиты		IP55
подходит для ширины		600
подходит для высоты		1600

Технические характеристики согласно ETIM 6.0

Cabinet enclosures (EG000011) / Door/operating panel (switchgear cabinet) (EC000747)		
Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Door (electrical cabinet) / Door/operating panel (enclosure) (ecl@ss8.1-27-18-22-04 [ACN614008])		
Model		Stop door
Version as glazed door		No
Version as door for disconnecting switch interlocking		No
Width	mm	593
Height	mm	1540
Depth	mm	40
EMC-version		Yes
Material		Steel
Type of surface		With powder coating
Colour		Grey
Degree of protection (IP)		IP55