



Тестовый модуль, 0,5А

Тип **Z-FW/050**
Каталог № **248301**
Eaton Каталог № **Z-FW/050**

Abbildung ähnlich

Программа поставок

Основная функция			Принадлежности для устройства защиты от аварийного тока
Основная функция дополнительного оснащения			Дистанционные проверочные модули
Применение			Коммутационные устройства для промышленного оборудования и специальных зданий
Расчетный ток утечки	$I_{\Delta N}$	A	0,5
Ассортимент			Принадлежности
Возможность установки			возможна установка слева на: FI

Bauartnachweis nach IEC/EN 61439

Технические характеристики для подтверждения типа конструкции			
Мин. рабочая температура		°C	-5
Макс. рабочая температура		°C	40

Технические характеристики согласно ETIM 6.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary contact unit for distribution board (EC001286)			
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss8.1-27-14-35-02 [AKE327010])			
Device fitting			Earth leakage switch
Additional equipment			Monitoring unit
Attached at delivery			No
Assembly width (TE)			0.5
Number of normally open contacts			0
Number of normally closed contacts			0
Number of change-over contacts			0
Number of fault-signal switches			0
Rated switch current		A	0
Nominal rated voltage		V	0
Control voltage type			AC
With autotest for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			0
Suitable for max. current main contact unit		A	0

