

Push-in terminal blocks-UJ6-10-421510



Terminal block, Rated voltage(V): 1000V, Rated current: 57A, connection methods: circlip connection, number of connection: 2, crimping range: 1.5mm² - 16mm², AWG : 16-6, thickness 10.2mm, height 67.7mm, color: grey, mounting rail: TH35-7.5、TH35-15.

Product parameter

Parameter	Data
Packing unit(pcs)	/
NW per piece(g)	/
Layers	1
Number of connections	2
Rated cross section(mm ²)	10
Color	grey
Insulation material	PA
Flame retardant grade	V0
Rated voltage(V)	1000
Rated current(A)	57
Temperature of insulation material	-40 ~ +125
Wire feed	Above the terminal

Product certification

Parameter	Data
Certification logo	CE
Certification logo	cUL [®] US
Certification logo	

Parameter	Data
	RoHS

Technical data

Parameter	Data
Connection Method	Push in connection
Stripping length(mm)	17
Solid conductors(mm ²)	1.5-16
Solid conductors AWG	16-6
Stranded conductors(mm ²)	1.5-10
Stranded conductors AWG	16-8
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +55
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	67.7
Thickness(mm)	10.2
Height(mm)	49.6