

Push-in terminal blocks-UJ6-2.5/1  
2JD-421464





线端子，接线方式：卡簧连接，连接量：3，  
压线范围：0.2mm<sup>2</sup> -4mm<sup>2</sup>，AWG：26-12，  
厚度5.2mm，高度35.2mm，颜色：黄绿，安  
装方式：TH35-7.5、TH35-15

Terminal block, connection methods: circlip  
connection, number of connection: 3, crimping ra  
nge: 0.2mm<sup>2</sup> -4mm<sup>2</sup>，AWG：26-12，thick  
ness 5.2mm, height 35.2mm, color: yellow green,  
mounting rail: TH35-7.5、TH35-15

## Product parameter

Parameter	Data
Packing unit(pcs)	100
NW per piece(g)	10.5
Layers	1
Number of connections	3
Rated cross section(mm <sup>2</sup> )	2.5
Color	yellow green
Insulation material	PA
Flame retardant grade	V0
Rated voltage(V)	/
Rated current(A)	/
Temperature of insulation material	-40 ~ +125
Wire feed	Above the terminal

## Product certification

Parameter	Data
Certification logo	
Certification logo	
Certification logo	

Parameter	Data
	<b>RoHS</b>

## Technical data

Parameter	Data
Connection Method	Push in connection
Stripping length(mm)	13
Solid conductors(mm <sup>2</sup> )	0.2-4
Solid conductors AWG	26-12
Stranded conductors(mm <sup>2</sup> )	0.2-2.5
Stranded conductors AWG	26-14
Operating temperature ( )	-40 ~ +105
Ambient temperature (storage/transportation) ( )	-25 ~ +55
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

## Dimension

Parameter	Data
Width(mm)	60.4
Thickness(mm)	5.2
Height(mm)	35.2