



Приоритетное реле, 8А

Тип **Z-LAR8-S**
Каталог № **248259**

Abbildung ähnlich

Технические характеристики согласно ETIM 6.0

| Devices for distribution board-/surface mounting (EG000062) / Load shedding relay for distribution board (EC001655) | | |
|---|--------------|----------|
| Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Load shedding relay for distribution board (ecl@ss8.1-27-14-23-32 [ACN383008]) | | |
| Nominal rated voltage | V | 250 |
| Rated current I _u | A | 3 - 8 |
| Just-operate current | A | 3 - 8 |
| Max. time-delayed switch-off | ms | 0 |
| Max. continuous current | A | 10 |
| Number of normally open contacts | | 1 |
| Number of normally closed contacts | | 0 |
| Number of change-over contacts | | 0 |
| Rated current (control contacts) | A | 1 |
| Max. switching voltage (control contacts) | V | 250 |
| Max. switching power (control contacts) | VA | 7.7 |
| Electrical lifespan (control contacts) | c (contacts) | 100000 |
| Mechanical lifetime (control contacts) | c (contacts) | 0 |
| Max. electrical operating cycles | c/h | 3600 |
| Voltage type | | AC |
| Mounting method | | DIN rail |
| Width in number of modular spacings | | 1 |
| Built-in depth | mm | 60 |
| Degree of protection (IP) | | IP20 |